



Installation instructions on a plasterboard wall

Before starting the installation of Artofix tiles, make sure you refer to your configuration diagram provided with order.

The installation steps are simple and easy to follow. The key to any install is to ensure that your first tile alignment is perfectly level. To achieve the best level plane possible, you should continue to check every 3 or 4 tile as you install them in first vertical (columns) and horizontal (rows) alignments.


NOTE: Our qualified technicians are available to assist with any installation project and will have all the necessary tools, equipment and experience to make a success of any install project.



1. Add adhesive caulking on the rear of the ARTOTRIM-L1 trim and affix to the wall.



2. If desired, fasten the trim to the wall by using screws or 1/2" (12mm) staples.




3. Draw your horizontal reference lines on wall or use a laser to level the row of tiles to be installed. Repeat this step for each new row.




4. Cut the tabs off the identified tiles on your plan that will go along the trims, by using a utility knife or scissors.



5. Then, install ARTOCLIPS-G1 on the side of where the tabs have been cut. The ARTOCLIPS-G1 facilitate the installation of tiles where the stapler can't be used.



6. Remove the protective paper on the back of ARTOCLIPS-G1. The tile is now ready to be installed.



7. For the tiles that will be fit onto the trim ARTOTRIM-L1, use a transparent silicone caulking to fasten them into the trim.




8. Put the first tile on the ARTOTRIM-L1, staple all the visible tabs on the tile making sure the tiles are aligned.




9. Continue the installation and verify the tile alignment using your reference line or laser in order to obtain a symmetrical finish.



10. If the tiles need to be cut to the bottom edge of the wall, cut the excess off and use the ARTOTRIM-C1 and an adhesive caulking to finish.



11. Firmly press the ARTOTRIM-C1 against the wall and add screws to fasten the trim to the wall.



12. Measure the tile size requirement to insert in the ARTOTRIM-C1.



13. Cut the tile to the required size using a utility knife.



14. Insert the tile bottom in the ARTOTRIM-C1 and strips in the upper tiles.



15. Repeat the process as necessary.



Installation instruction (HELPFULL TOOLS & HARDWARES)

